



**- PAPER LABEL PORTFOLIO**

Material Name	Printing Technology	Key Features	Spec Sheets	Compatible Ribbon Formulation
<b>Z-Perform 1000D</b>	Direct Thermal	Standard uncoated label. Not recommended for exposure to moisture.	<ul style="list-style-type: none"> <li>• <a href="#">Z-Perform 1000D – Permanent</a></li> </ul>	N/A
<b>Z-Perform 1000D PF</b>	Direct Thermal	Uncoated phenol-free paper label.	<ul style="list-style-type: none"> <li>• <a href="#">Z-Perform 1000D PF</a></li> </ul>	N/A
<b>Z-Perform 1500T</b>	Thermal Transfer	Standard coated label. Some moisture and weak chemical (i.e. window cleaner) resistance. Can withstand temperatures from 0°F (-18°C) to 180°F (82°C).	<ul style="list-style-type: none"> <li>• <a href="#">Z-Perform 1500T – Permanent Adhesive</a></li> </ul>	<ul style="list-style-type: none"> <li>• 1600 Wax</li> <li>• 6000 Wax</li> <li>• 2000 Wax</li> <li>• 6100 Wax/Resin</li> </ul>
<b>Z-Perform 2000D</b>	Direct Thermal	Standard coated label. Some moisture and weak chemical (i.e. window cleaner) resistance. Can withstand temperatures from -65°F (-54°C) to 200°F (93°C).	<ul style="list-style-type: none"> <li>• <a href="#">Z-Perform 2000D – Permanent Adhesive</a></li> </ul>	N/A
<b>Z-Perform 2000T</b>	Thermal Transfer	Standard coated label. Some moisture and weak chemical (i.e. window cleaner) resistance. Can withstand temperatures from -65°F (-54°C) to 200°F (93°C).	<ul style="list-style-type: none"> <li>• <a href="#">Z-Perform 2000T – Permanent Adhesive</a></li> <li>• <a href="#">Z-Perform 2000T – All-Temp Adhesive</a></li> </ul>	<ul style="list-style-type: none"> <li>• 1600 Wax</li> <li>• 6000 Wax</li> <li>• 2000 Wax</li> <li>• 6100 Wax/Resin</li> </ul>
<b>Z-Select 4000D</b>	Direct Thermal	Premium coated label. Some moisture and weak chemical (i.e. window cleaner) resistance.	<ul style="list-style-type: none"> <li>• <a href="#">Z-Select 4000D – All-Temp Adhesive</a></li> </ul>	N/A
<b>Z-Select 4000T</b>	Thermal Transfer	Premium coated label. Some moisture and weak chemical (i.e. window cleaner) resistance. May be used across a wide temperature range.	<ul style="list-style-type: none"> <li>• <a href="#">Z-Select 4000T – Permanent Adhesive</a></li> <li>• <a href="#">Z-Select 4000T – All-Temp Adhesive</a></li> <li>• <a href="#">Z-Select 4000T – Removable Adhesive</a></li> </ul>	<ul style="list-style-type: none"> <li>• 1600 Wax</li> <li>• 6000 Wax</li> <li>• 2000 Wax</li> <li>• 6100 Wax/Resin</li> </ul>
<b>IQ Color 2000D</b>	Direct Thermal	Ability to print vibrant color on demand in pre-defined zones. Not recommended for exposure to moisture. Available in standard and opaque paper labels.	<ul style="list-style-type: none"> <li>• <a href="#">IQ Color 2000D – Permanent Adhesive</a></li> <li>• <a href="#">IQ Color 2000D – All-Temp Adhesive</a></li> <li>• <a href="#">IQ Color 2000D – Removable Adhesive</a></li> <li>• <a href="#">IQ Color 2000D – Opaque Material</a></li> </ul>	N/A